

4400-H SERIES



- 30,000 LBS. CAPACITY
- FULL TIME FOUR WHEEL DRIVE
- OUTBOARD PLANETARY DRIVE AXLES
- OIL IMMERSED DISC BRAKES
- HEAVY DUTY POWERSHIFT TRANSMISSION
- SIX CYLINDER EPA COMPLIANT ENGINE
- MODULAR COOLING SYSTEM
- HEAVY DUTY C-THRU ROLLER MASTS
- SUPERIOR OPERATOR VISIBILITY
- CERTIFIED F.O.P.S. STRUCTURE
- FULL RANGE OF ATTACHMENTS AVAILABLE

4414-30H complete with sideshifting fork positioner

LOAD LIFTER FEATURES DO WORK FOR YOU

SPECIFICATIONS

MACHINE APROX. WEIGHTS

24,091 kg. (53,000 lbs)

MACHINE DIMENSIONS

A (Tilt Back) 14°

B (Tilt Forward) 18°

C (Machine Ground Clearance) 17"

D (Mast Ground Clearance) 11 1/2"

E (Counterweight Overhang) 70"

F (Wheelbase) 155"

G (C/L Drive Axle to Face of Forks) 54"

H (Overall Length to Face of Forks) 280"

I (Overall Height Top of Cab) 138"

J (Turning Clearance) 261"

K (Turning Radius) 247"

L (Overall Width) 110"



Make FPT N67 250 hp

Displacement 6.7 liters

B.H.P. 250 hp (187KW)

Maximum Torque 1147 NM Rated Speed 1400 RPM

TRANSMISSION

Type 4F/4R Speed T14,000 Series

Maximum Speeds 1. 4.2 km/h (2.6 mph) 2. 9 km/h (5.6 mph)

3. 20 km/h (12.5 mph)

4. 27 km/h (17 mph)

HYDRAULIC SYSTEM

Pump Tandem Gear Type System
Full Load Sense Steering Circuit

Modular Control Valve c/w Tilt Lock System

ELECTRICAL SYSTEM

Volts 12 Alternator 100 Amp.

FLUID CAPACITIES

TURNING CLEARANCE "J"

Cooling Systems Engine Oil Fuel Hydraulic Oil Brake Cooling Tank 15.5 liters (12.2 Quarts) 15.1 liters (16 Quarts) 189.5 liters (50 US Gallons) 215 liters (56.8 US Gallons) 65 liters (17.17 US Gallons)

BRAKE

00000

TURNING -RADIUS

Hydraulic Power Oil Immersed disc brakes

AXLES

Drive/Steer

Kessler Outboard Planetary 4 Wheel Drive

TIRES

Drive/Steer 18:00 x 25R

STANDARD EQUIPMENT

- 4F/4R Speed T14,000 Series Transmission
- Electric Column Shift
- Tilt & Telescopic Steering Console
- Hydrostatic Power Load Sense Steering
- Safety Start
- Dry Type Air Cleaner
- Retractable Seat Belts
- Height Adjustable Seat c/w Arm Rests
- Engine Temp
- Engine Oil Pressure
- Fuel Level
- Water Temp.Power Brakes
- Air Ride Swivel Seat
- F.O.P.S. Cab

- Hour meter
- Circuit Breakers
- Block Heater
- Heavy Duty Battery
- Anti-Freeze -40°C
- Horn
- Four Work Lights
- Directional signals
- Marker lights
- Reverse lights
- Brake lights
- Transmission De Clutch
- 14' C-Thru Mast
- 60" Shaft Carriage
- 48" Forks
- Load Lifter Touch Screen Display
- Windshield Washer Kit

OPTIONAL EQUIPMENT

- Mirrors
- Air Conditioning
- Cold Weather Package
- High Air intake
- Cyclonic Pre-Cleaner
- Lift Circuit Cushion Accumulator
- Pintle Hook
- Fork Positioners
- Load Grapples
- Hydraulic Bucket
- Full Range of Attachments



This information contained herein is general in nature and not intended for specific application purpose. Load Lifter reserves the right to make changes in specifications, make improvements, or discontinue manufacture at any time without notice or obligation